



Electronic Auto-Compensation

| Seismograph system

Details Info

Main Application:

By utilizing the apparent resistivity parameters, it is widely used in hydrology, environmental protection, engineering geophysical exploration, metal and non-metal mineral resources exploration

Main Features:

Microcomputer controlled, direct-reading resistivity, various electrode arranging mode, data protection against power-failure

Main Technical Specification

Maximum Power Supply Voltage	700V
Maximum Power Supply Current	4A
Voltage Measuring Range	±4V
Voltage Measurement Accuracy	±1%±1 digit
Current Measuring Range	0~4A
Current Measurement Accuracy	±1%±1 digit
SP Compensation Range	-1000mV ~ +1000mV

Instrument Input Impedance	>8MΩ
Working Temperature	-10°C~50°C
Volume	300×200×120mm



Head Office :1600 AVENUE DE LORIMIER BUREAU, 384 MONTRÉAL (QUÉBEC) CANADA H2K3W8 USAOffice:128 W SUFFLOK AVE,CENTRAL ISLIP,11722 N Middle east & Africa Office : warehouse 9 /shed 9, Technology park P.O. Box 54806 RAK FZE , UAE



Email Us At:

sales@acculabusa.com middleeast@acculabusa.com



Phone Support:

© Copyright 2014 by ACCULAB_USA - All rights reserved