



SLM-100

| Sound level meter

☰ Details Info

Features:

Applied standard : IEC61672-1 CLASS2

Frequency weighting: A and C

Time weighting: FAST and SLOW

MAX/MIN record

Data Hold

Overrange indication

analog bar-graph indication

Specifications:

Applied standard	IEC61672-1 CLASS2
Accuracy	±1.4dB
Frequency range	31.5Hz~8kHz
Dynamic range	50dB

Measuring level range	Lo: 30dB~80dB Med: 50dB~100dB Hi: 80dB~130dB Auto: 30dB~130dB
Frequency weighting	A and C
Time weighting	FAST 125ms; SLOW (1s)
Microphone	1/2 inch electret condenser microphone
Resolution	0.1dB
Sampling time	2 times/second
MAX hold	MAX
MIN hold	MIN
DATA hold	HOLD
Overrange indication	"OVER" or "UNDER"
Backlight display	√
Analog measurement	fast analog bar-graph indication
Operating conditions	-20°C~+60°C: 10%RH~90%RH
Storage conditions	-20°C~+60°C: 10%RH~75%RH
Auto power off	the meter will be automatically shut off in activity of 15 minutes



Head Office :1600 AVENUE DE LORIMIER BUREAU, 384 MONTRÉAL (QUÉBEC) CANADA H2K3W8 USAOffice:128 W SUFFLOK AVE,CENTRAL ISLIP,11722 N
Middle east & Africa Office : warehouse 9 /shed 9, Technology park P.O. Box 54806 RAK FZE , UAE



Email Us At:

sales@acculabusa.com middleeast@acculabusa.com



Phone Support: